

Lotus 12mil Glue Down

TECHNICAL DATA

EVOLUX[®]
LUXURY EVOLVING

11190 NW 25th Street, Suite 100
MIAMI, FL 33172
www.rocatileusa.com

Format:	7"x48"	Type:	Virgin Vynil
Colors:	BLONDE, MAPLE, ASH, SNOW, TAUPE, COCOA.	Thickness:	2.0 mm
		Wear Layer	12 mil

	Standard	Result
SURFACE TREATMENT		Diamond Guard / Health Guard
SURFACE TEXTURE		Wood Emboss
WARRANTY	Commercial / Residential	10 year Light Commercial / Limited Lifetime Residential
INSTALLATION		Glue down
BEVELED EDGE		No
CLASSIFICATION	ASTM F1700	Class III Type B
REACTION TO FIRE	ASTM E648-06	Class 1
SMOKE DENSITY	ASTM E662-06	Pass <450
SLIP RESISTANCE	ASTM C1028	Pass ADA Compliant (>0.50)
STAINING RESISTANCE	ASTM F925	Pass
LIGHT RESISTANCE	ASTM F1514	Pass
ABRASION RESISTANCE	ASTM D4060	Pass
DIMENSIONAL STABILITY	ASTM F2199	Pass 0.011 in / ft <0.020 in / ft
ACOUSTIC IMPACT NOISE REDUCTION	ASTM E2179-09 ASTM E492-09	ΔIIC = 4 dB
STATIC LOAD	ASTM F970	Pass 1000 psi / 250 psi (<0.005 in)
FLEXIBILITY	ASTM F137	Pass
PHthalate FREE		Yes



Signature:
Marketing and Product Department

Roca
MARKETING & PRODUCT DEPT
11190 NW 25th Street, Suite 100
MIAMI, FL 33172
www.rocatileusa.com

Release
05 / 01 / 2024